



DRYING PROCESS

Vacuum dry process for Wood

With our drying process, we want to offer our clients the best quality in all our pieces. The drying process it's done in vacuum drying machines which led us removing all the humidity of the wood in a fast way and at the best conditions, because the pieces don't suffer any kind of flaw or imperfection.

To accomplish our but, we use advanced technology for wood treatment: vacuum drying machines with PCL system, with which we guarantee a high standard of quality.

This process is also indicated to dry wood with special characteristics because with this vacuum dry system, the wood is never exposed to climate aggressions like air stream, which could harm the wood during the drying process.

Our achievement is that we satisfy any exigence of our clients at the same time that we adapt our work to their needs.

Grade of humidity achieved during the process

After the drying process, the grade of humidity we achieve in our pieces is between 8% and 10%.

We recommend that when you acquire the wood after a drying process, the pieces must be stored in a place where humidity is controlled, since the wood is a material which can easily take up humidity again, even after a drying process.

Important note: Orders with this option can suffer variations regard to delivery times, since the wood in our stock is not dry.

If you need more information about the drying process of our wood, don't hesitate in contact us. We will be pleased to answer you any question personally in our offices, through our telephone number (+34) 96 134 03 01 or via email:

info@maderas-barber.com.

MADERAS BARBER

C/ Islas Baleares 42

P. I. Fuente del Jarro

46988 - Paterna (Valencia)

SPAIN